HEAT TORCH




Shown with optional inlet & exhaust fittings

- The Heat Torch™ 200 inline heater is engineered to satisfy the most demanding requirements. It is contained in a 2" diameter stainless steel pipe and is available in three sizes. The 5" long heater body is for power ratings from 1000 to 4250 watts (with power increments of 250 watts). The 9" long is for power ratings of 4500 to 8500 watts (with standard power increments of 500 watts). The 13" long heater is for power ratings from 9000 to 12500 watts (with standard power increments of 1000 watts).
- The Heat Torch™ 200 has an allowable air flow ranging from 9.6 to 100 SCFM . Maximum air input temperature is 250°F (121°C) with 1300°F (704°C) the maximum output temperature. Standard inlet fitting is a 1" NPT female. Standard outlets are 1 1/4" female NPT fitting or no exhaust fitting.

	Wattage	Min. SCFM Req.
	1.0kW	9.6
	4.0kW	9.6
	5.0kW	12.4
	6.0kW	14.8
	7.0kW	17.0
	8.0kW	19.3
	9.0kW	21.4
	10.0kW	23.5
	11.0kW	25.5
	12.5kW	28.4

Airflow (SCFM)	0.5kW- 4.25kW Pressure Drop (psig)	4.5kW- 8.5kW Pressure Drop (psig)	8.75kW- 12.5kW Pressure Drop (psig)	
10	.36	.72	1.1	
20	.75	1.5	2.3	
30	1.7	3.4	5.1	
40	3.0	6.0	9.0	
50	4.7	9.4	14	
60	6.8	14	20	
70	9.2	18	28	
80	12	24	36	
90	15	30	45	
100	19	38	57	



Wattage	Heater Body Dim. A	Exhaust Fitting	Dim. B	
1.0kW-4.25kW	5.0	1 1/4F	1.13	
4.5kW-8.5kW	9.0	NF	0.10	
8.75kW-12.5kW	13.0			

2.Al						
	Wattage	Heater Body Dim. A	Exhaust Fitting	Dim. B		
	1.0kW-4.25kW	5.0	1 1/4F	1.13		
	4.5kW-8.5kW	9.0	NF	0.10		
	8.75kW-12.5kW	13.0				

		_		,				
		Pa	rt Nun	nber Ke	у			
HT200	1000	120	1	1F	NF	TF1	(XXX)	
						Fitting		
_						這		

H1200	1000	120	1	1F	NF	IFT	(XXX)
Heat Torch 200	Wattage	Voltage	Phase	Inlet Fitting	Exhaust Fitting	Thermocouple Fitting	Modification



Wattage & Voltage Options

120V, single phase, 1.0kW-2.5kW 240V, single phase, 1.0kW-8.5kW 240V, three phase, 4.5kW-12.5kW 480V, single phase, 4.5kW-12.5kW 480V, three phase, 1.5kW-12.5kW

Other Options

Thermocouple Fitting Thermocouple Flexible Conduit

Specifications

Category: Inline Heaters,

Process Heaters, Open Coil Heaters

Inlet Fitting:

1F- 1" FNPT

Exhaust Fitting:

NF- No Fitting

1 1/4F- 1 1/4" FNPT

Fitting Options

Max. wattage: 12.5kW Max. exhaust air temp.: 1300°F Max. inlet air temp.: 250°F (consult factory for higher inlet temp.)

Max. SCFM: Pressure Rating: 120 psig Mounting: Horizontal/Vertical 12 gauge (12" long) Leads: Heater Body: Stainless Steel

Inlet Fitting: Stainless Steel Exhaust Fitting: Stainless Steel

16 Revised 9/29/2010

9001:2008