

# High Pressure Heated Hose

Style CH60 Hose Cores - High Pressure  
Smooth Bore PTFE Teflon

## FEATURES:

- Overall Strength and Reliability
- Flexible, lightweight design
- Conductive 0.040" wall PTFE Teflon® Innercore for Static Dissipation
- Exceptional margin of safety

## YOUR BEST CHOICE FOR:

- Chemical Plants
- Industrial Gases
- Adhesives and Automotive Manufacturing Processes
- Petrochemical Sites
- Glass and Window Manufacturing Conrad smooth bore PTFE Teflon® inner core for high-pressure applications.

HOSE SIZE	AVERAGE I.D. (IN.)	MAXIMUM OPERATING	BURST PRESSURE	MINIMUM BEND
--------------	-----------------------	----------------------	-------------------	-----------------

		PRESSURE @ 70OF (PSI)	@ 70OF (PSI)	RADIUS (IN.)
CH60-04	0.222	3000	16000	1.5
CH60-06	0.308	3000	16000	2.5
CH60-08	0.401	3000	16000	2.9
CH60-10	0.495	3000	16000	3.3
CH60-12	0.617	3000	16000	4
CH60-16	0.867	3000	16000	5
CH60-20	1.112	3000	16000	12
CH60-24	1.375	3000	12000	14