

Stainless Steel Corrugated Heated Hose

Style CH92 Hose Cores

Features:

- High Temperature to 750 F
- Flexible Design
- High-Density Thermal Insulation
- Exceptional Margin of Safety

Your Best Choice For:

- Foundries
- Investment Casting
- Industrial Gases

Core Part Number	Inside Diameter (in.)	Number Of Braids	Static Min. Bend Radius (in.)	Working Pressure (p.s.i.)	Burst Pressure (p.s.i.)
CH92-1/4	0.25	1	0.9	1800	7233
CH92Z-1/4	0.25	2	0.9	2700	9100
CH92-3/8	0.38	1	1	1558	6230
CH92Z-3/8	0.38	2	1	1336	9345
CH92-1/2	0.5	1	1.2	1186	4743
CH92Z-1/2	0.5	2	1.2	1779	7115
CH92-5/8	0.63	1	1.4	1205	4820
CH92Z-5/8	0.63	2	1.4	1808	7230
CH92-3/4	0.75	1	1.7	898	3591
CH92Z-3/4	0.75	2	1.7	1347	5387

CH92-1	1	1	2.1	718	2872
CH92Z-1	1	2	2.1	1077	4308
CH92-1.1/4	1.25	1	2.5	645	2581
CH92Z-1.1/4	1.25	2	2.5	968	3872
CH92-1.1/2	1.5	1	3.1	531	2125
CH92Z-1.1/2	1.5	2	3.1	797	3188
CH92-2	2	1	4	449	1797
CH92Z-2	2	2	4	674	2696
CH92-2.1/2	2.5	1	5.4	417	1669
CH92Z-2.1/2	2.5	2	5.4	626	2504
CH92-3	3	1	6.3	346	1384
CH92Z-3	3	2	6.3	519	2076
CH92-4	4	1	7.7	299	1194
CH92Z-4	4	2	7.7	448	1791
CH92-5	5	1	10	275	1099
CH92Z-5	5	2	10	412	1649
CH92-6	6	1	11.6	210	839
CH92Z-6	6	2	11.6	315	1259