

DL & EL Series Connection Accessories

DL Series

- Re-usable Components
- Through-the-Insulation Mounting Provides High Visibility
- Easy Access for Maintenance

EL Series

- Low Profile Provides Easy Installation of Insulation
- Contains Standard, Off-the-Shelf Electrical Connection Components

Chromalox offers cable termination kits in DL for high profile, through-the-insulation styles and EL for low profile, under-the-insulation. Both styles are approved for hazardous area applications.



Phone: 704-399-4248
Fax: 704-399-4167
sales@sethermal.com



RTPC



RTST



RTES



Ordering Information

DL Accessories		EL Accessories	
Model	Used With	Model	Used With
Power Connection Kit			
RTPC RTPC-SL	SRL-C SRL-CR, CT SRP-C, SRP-CT CWM-C CWM-CT SRL-MC SRL-MCR, MCT SRM/E-C SRM/E-CT	SSK PJB RG-PK-1	SRL-C, SRL-CR, SRL-CT, SRF-C, CWM-C, CWM-CT SRF-RG SRP-C, SRP-CT HWM
Splice & Tee Kit			
RTST RTST-SL	SRL-C SRL-CR, CT SRP-C, SRP-CT CWM-C CWM-CT SRL-MC SRL-MCR, MCT SRM/E-C SRM/E-CT	RT-RST RT-TST RG-SK-1	SRL-C, SRL-CR, SRF-C CWM-C, CWM-CT SRF-RG, SRP-C SRP-CT
End Seal Kit			
RTES	SRL-C SRL-CR, CT SRP-C, SRP-CT CWM-C CWM-CT SRL-MC SRL-MCR, MCT SRM/E-C SRM/E-CT	RT-RES RG-EK-1	SRL-C, SRL-CR, SRF-C SRF-RG
To Order — Refer to the DL & EL General Application Accessories in this section.			

Attachment Accessories

Model	Description
FT-3	Fiberglas® tape to affix cable to pipe
AT-1	Aluminum tape to improve heat transfer to pipe
PS-1	Pipe strap to mount power connection box to pipe, 1/2 - 3/4" pipes
PS-3	Pipe strap to mount power connection box to pipe, 1 - 3-1/2" pipes
PS-10	Pipe strap to mount power connection box to pipe, 2-1/2 - 9" pipes
CL-1	Caution labels, apply every 10 feet to insulation to alert personnel
To Order — Refer to the DL & EL General Application Accessories in this section.	

DL & EL Series

General Application Accessories

Accessories



**Conduit Hub
Cable Attachments
CCH-2 (385650)**

Corrosion resistant for 3/4" conduit. Fits opening in RTPC and PJB. Includes a ground connector.



**Metal Pipe Strap Kit
Attachments
PS-1, 3 and 10**

PS-1 (382352) 1/2 to 3/4" pipes
PS-3 (382360) 1 to 3-1/2" pipes
PS-10 (382379) 2-1/2 to 9" pipes

Interlock Straps for larger diameter pipes



**Fiberglass® Tape
Cable Attachments
FT-3 (389941)**

66 foot roll glass cloth tape with pressure-sensitive thermosetting silicone adhesive 3/8" wide. 310°F (155°C) rating. Strap at one foot intervals at minimum application temperatures of -40°F (-40°C).



**Caution Labels
CL-1 (382424)**

5 electric heat tracing caution labels, weather resistant.



**Aluminum Tape
Cable Attachments
AT-1 (383355)**

180 foot roll aluminum foil installation tape with pressure-sensitive acrylic adhesive. 2-mil thickness with high tensile strength; 2-1/2" wide. 200°F (93°C) rating. Minimum application temperatures 40°F (5°C).

Ordering Information — Cable Attachments

Description	Model	PCN	Stock	Wt. (Lbs.)
Fiberglass® Tape	FT-3	389941	S	1
Aluminum Tape	AT-1	383355	S	2
Metal Pipe Strap Kit	PS-1	382352	S	1
	PS-3	382360	S	1
	PS-10	382379	S	1
Caution Labels	CL-1	382424	S	1
Cable Stripping Tool with 16 awg blades	ST-1	393510	S	1
14 awg Replacement Blades	BL-1	393529	S	1
16 awg Replacement Blades	BL-2	393537	S	1
20 awg Replacement Blades	BL-3	393545	S	1
To Order – Specify model, PCN and quantity.				



**Cable Stripping Tool
w/16 awg Blades
ST-1 (393510)**

Replacement Blades

BL-1 14 awg (393529)

Blades for use with the Cable Stripping Tool. 14 awg blades for HSRM and SRM/E products.

BL-2 16 awg (393537)

Blades for use with the Cable Stripping Tool. 16 awg blades for HSRL and SRL, SRF and Thermwire products.

BL-3 20 awg (393545)

Blades for use with the Cable Stripping Tool. 20 awg blades for SRR, SRS and STW products.

