

Ceramic Infrared Price List

Part Number	Length		Width		Watts	Volts	Std. Lead Length	TC
	mm	in	mm	in				
FSR/4-250-230	60	2.362	60	2.362	250	230	85	NO
FSR/2-325-230	122	4.803	60	2.362	325	230	85	NO
FSR/2-352-230-BLACK	122	4.803	60	2.362	325	230	85	NO
FSR/2-325-230-YELLOW	122	4.803	60	2.362	325	230	85	NO
FSR/2-500-230	122	4.803	60	2.362	500	230	85	NO
FSR/2-500-230-BLACK	122	4.803	60	2.362	500	230	85	NO
FSR/2-500-230-YELLOW	122	4.803	60	2.362	500	230	85	NO
T-FSR/2-325-230	122	4.803	60	2.362	325	230	85	K
T-FSR/S-325-230-BLACK	122	4.803	60	2.362	325	230	85	K
T-FSR/2-325-230-YELLOW	122	4.803	60	2.362	250	230	85	K
FSR-1000-230	122	4.803	60	2.362	500	230	85	K
T-FSR/2-500-230-BLACK	122	4.803	60	2.362	500	230	85	K
T-FSR/2-500-230-YELLOW	122	4.803	60	2.362	500	230	85	K
FSR-1000-230	245	9.646	60	2.362	1000	230	85	NO
FSR-1000-230-BLACK	245	9.646	60	2.362	1000	230	85	NO
FSR-1000-230-ROSE	245	9.646	60	2.362	1000	230	85	NO
FSR-1000-230-YELLOW	245	9.646	60	2.362	1000	230	85	NO
FSR-1000-480-BLACK	245	9.646	60	2.362	1000	480	85	NO
FSR-400-230	245	9.646	60	2.362	400	230	85	NO
FSR-650-230	245	9.646	60	2.362	650	230	85	NO
FSR-650-230-BLACK	245	9.646	60	2.362	650	230	85	NO
FSR-650-230-YELLOW	245	9.646	60	2.362	650	230	85	NO
FSR-650-480-BLACK	245	9.646	60	2.362	650	480	85	NO
T-FSR-1000-230	245	9.646	60	2.362	1000	230	85	NO
T-FSR-1000-230-BLACK	245	9.646	60	2.362	1000	230	85	K

T-FSR-1000-230-ROSE	245	9.646	60	2.362	1000	230	85	K
T-FSR-1000-230-YELLOW	245	9.646	60	2.362	1000	230	85	K
T-FSR-1000-480-BLACK	245	9.646	60	2.362	1000	230	85	K
T-FSR-400-230	245	9.646	60	2.362	400	230	85	K
T-FSR-650-230	245	9.646	60	2.362	650	230	85	K
T-FSR-650-230-BLACK	245	9.646	60	2.362	650	230	85	K
T-FSR-650-230-YELLOW	245	9.646	60	2.362	650	230	85	K
T-FSR-650-480-BLACK	245	9.646	60	2.362	650	480	85	K
HSR/2-500-230	122	4.803	60	2.362	500	230	85	NO
HSR-1000-230	125	4.921	125	4.921	1000	230	85	NO
HSR/1-1000-230	245	9.646	60	2.362	1000	230	85	NO
HTS/2-500-230	122	4.803	60	2.362	500	230	85	NO
T-HTS/2-500-230	122	4.803	60	2.362	500	230	85	K
HTS-1000-230	122	4.803	122	4.803	1000	230	85	NO
T-HTS-1000-230	122	4.803	122	4.803	1000	230	85	K
HTS/1-1000-230	245	9.646	60	2.362	1000	230	85	NO
HTS/1-400-230	245	9.646	60	2.362	400	230	85	NO
T-HTS/1-1000-230	245	9.646	60	2.362	1000	230	85	K
IOT/90-250-230	90 MM(3.453 INCHES)				250	230	85	NO

245mm x 60mm



122mm x 60mm



122mm x 122mm

60mm x 60mm



90mm or 60mm (IOT)

