

704-399-4248

WWW.SETHERMAL.COM

Customer Name:	
Completed by:	Date:
Contact Number:	Quantity:
Job Number:	Part Number:

Ceramic Band Heater Spec Build Sheet

* REQUIF	RED						
*Style:	Full	Half	Partial	Agency approvals:	None	CE	CSA
	Strip	Other		U.L. Component Recognized			
* Inside Diame	eter:	inches	mm		Other:		
* Width:		inches	mm	Special Features: Hole	s/Cutouts (spec	cify size, location), Grounded
*Watts:	total/each 1/2			terminal, Oversize Gap			
*Volts:	total/dual/3 phase						
*Insulation:	Standard 1	/4"	Double 1/2"				
	Air-Co	ooled Perforate	d Shroud	Operating Conditions:			
*Mounting:	Flange lock-up	Latch	and trunnion	Application: (describe			
	Barrel nut clamp	0	verlap flange				
*Termination:	Metal braide	d leads	Terminals				
	Armor Cab	ole	Ground wire				
*Lead length:		inches	mm	Heated medium:	Gas	Solid	Liquid
*Lead protecti	on:	inches	mm	Application temperatu	re:	° F	
*Termination location: Degrees from gap		Ambient temperature:		° F			
				Installation environme	nt: Indoo	or C	Outdoor