




| REV | | DESCRIPTION | BY | CHK |
|-----|----------|--|-----|-----|
| A | 11/11/15 | WEBSITE RELEASE | | MD |
| B | 01/27/16 | ADDED NOTES, REARRANGED ADJ. TOLERANCE | RLB | DEB |



| INLET FITTING | A | B | THERMOCOUPLE | C | EXHAUST FITTING | D | E |
|---------------------|-------|--------|--------------|--------|-----------------|--------|--------|
| NF | 9.81" | 0.094" | YES | 0.875" | NF | 0.094" | 1.216" |
| 1 1/4" | 9.81" | 1.125" | NO | 0 | 1 1/4" | 1.125" | 0.185" |
| $F = A + B + C + D$ | | | | | | | |

PART NUMBER CONSTRUCTION



- OPTIONAL MODIFICATION NUMBER IS ASSIGNED FOR CUSTOM CONFIGURATION.
- OPTIONAL TYPE K THERMOCOUPLES MAY BE ADDED WITH A THERMOCOUPLE COLLAR & OR 2 PROBE CONFIGURATION AVAILABLE
- EXHAUST FITTING OPTIONS ARE: 1-1/4" NPT OR NO-FITTING RING
EXHAUST FITTINGS ARE MADE FROM 303 OR 304 STAINLESS STEEL
- INLET FITTING OPTIONS ARE: 1-1/4" NPT OR NO FITTING RING
INLET FITTINGS ARE MADE FROM 303 OR 304 STAINLESS STEEL
- LEADWIRE IS 14 GA. BLACK 600V 200C UL1199
STANDARD 18" LEAD

NOTES: 1. USE WITH CLEAN DRY AIR SUPPLY

| CONFIDENTIAL | | THIRD ANGLE PROJECTION | SOUTHEAST THERMAL SYSTEMS | |
|---|----------------|---|---|-------------|
| THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF FARMAN CUSTOM PRODUCTS AND ITS RECEIPT OR POSSESSION DOES NOT CONVEY ANY RIGHTS TO REPRODUCE, DISCLOSE ITS CONTENTS, OR TO MANUFACTURE, USE, OR SELL ANYTHING IT MAY DESCRIBE. REPRODUCTION, DISCLOSURE, OR USE WITHOUT SPECIFIC WRITTEN AUTHORIZATION OF FARMAN CUSTOM PRODUCTS IS STRICTLY FORBIDDEN. | | ALL DIMENSIONS ARE IN INCHES, UNLESS OTHERWISE SPECIFIED. SCALE: 1/1 DO NOT SCALE DIMS. | TOLERANCES XX = ±.00 XXX = .005 ANGLES ±1/4° | |
| APPROV. BY: M. DULKEN | DATE: 11/12/15 | BY: M. MET | TITLE: FT200-1-1 1/4"-1 1/4"-TF2 | REV. A |
| | | | DWG. NO.: FT200 SHORT | REV. A |
| | | | DATE: 11/12/15 | REV. 1 OF 1 |
| | | | | REV. C |