

High Pressure Heated Hose

Style CH60 Hose Cores - High Pressure Smooth Bore PTFE Teflon

FEATURES:

- Overall Strength and Reliability
- Flexible, lightweight design
- Conductive 0.040" wall PTFE Teflon® Innercore for Static Dissipation

- Exceptional margin of safety

YOUR BEST CHOICE FOR:

- Chemical Plants
- Industrial Gases
- Adhesives and Automotive Manufacturing Processes
- Petrochemical Sites
- Glass and Window Manufacturing Conrad smooth bore PTFE Teflon® inner core for high-pressure applications.

| HOSE SIZE | AVERAGE I.D. (IN.) | MAXIMUM OPERATING PRESSURE @ 70°F (PSI) | BURST PRESSURE @ 70°F (PSI) | MINIMUM BEND RADIUS (IN.) |
|-----------|--------------------|---|-----------------------------|---------------------------|
| CH60-04 | 0.222 | 3000 | 16000 | 1.5 |
| CH60-06 | 0.308 | 3000 | 16000 | 2.5 |
| CH60-08 | 0.401 | 3000 | 16000 | 2.9 |
| CH60-10 | 0.495 | 3000 | 16000 | 3.3 |
| CH60-12 | 0.617 | 3000 | 16000 | 4 |
| CH60-16 | 0.867 | 3000 | 16000 | 5 |
| CH60-20 | 1.112 | 3000 | 16000 | 12 |
| CH60-24 | 1.375 | 3000 | 12000 | 14 |